

SYNTHETIC RESINS - PAINT AND VARNISH / Solvent Based

LONG OIL ALKYD RESIN

IZELKYD LO N 63X70

PRODUCT DESCRIPTION

Solvent based, long oil and oxidative drying alkyd resin High colour durability and gloss retention Very good yellowing resistance

STORAGE & SHELF LIFE

The resin should be stored indoors in original, unopened, undamaged container in a dry place at storage temperature between 5-30 °C Exposure to direct sunlight should be avoided. The shelf life of the resin under the mentioned storage conditions is 1 year.

DELIVERY FORM

COMPATIBILITY

Long oil alkyd resin Compatible IBC - 1000 kg Cellulose nitrate Compatible Barrel - 200 kg Bulk

Short oil alkyd resin Incompatible

Amino resins Compatible

MATERIAL SAFETY

SDS for this product is available on request

APPLICATION

Parquet varnishes Synthetic paints and varnishes

Wood

Construction paint

TECHNICAL SPECIFICATIONS

Property	Value	Unit	Test Method
Modification	Specific	-	-
Type of oil	Sunflower fatty acid	-	-
Oil percentage	63	%	-
Solvent type	Xylene	-	-
Solid content	69-71	%	TS EN ISO 3251
Viscosity (Gardner 25 °C)	S-V / 7,3-13	Gardner/sec	ASTM D 1545-13
Viscosity (60%, Gardner 25 °C)	F-H / 2,05-2,93	Gardner/sec	ASTM D 1545-13
Acid value	Max 11	mg KOH/g	TS 2366 EN ISO 2114
Colour (%50 Solid)	Max 7	Gardner	TS EN ISO 4630

SOLUBILITY

RECOMMENDED DRYER RATES

Acetone	Soluble	Cobalt	0,05-0,07 %
White spirit	Soluble	Zirconium	0,2-0,4 %
Xylene	Soluble	Calcium	0,1-0,3 %
Toluene	Soluble		

Recommended scatter rates over 100% solid alkyd metal percentages.

The information in this data sheet is to the best of our knowledge correct at the date of printing. They merely serve the purpose of informing our customers and do not relieve them from examining themselves the suitability of the described products for the intended purpose. Since conditions of the application are beyond our control, no liability can be accepted on the basis of this data sheet